



PhilGEPS

Philippine Government Electronic Procurement System

Central Portal for
Philippine Government
Procurement Opportunities

Bid Notice Abstract

Invitation to Bid (ITB)

Reference Number 10298225
Procuring Entity BAGUIO WATER DISTRICT - BAGUIO CITY
Title various water service connection fittings
Area of Delivery Benguet

Solicitation Number: 10-192P-B	Status	Pending
Trade Agreement: Implementing Rules and Regulations	Associated Components	1
Procurement Mode: Public Bidding	Bid Supplements	0
Classification: Goods	Document Request List	0
Category: Water Service Connection Materials/Fittings	Date Published	10/11/2023
Approved Budget for the Contract: PHP 4,765,085.50	Last Updated / Time	09/11/2023 10:50 AM
Delivery Period:	Closing Date / Time	06/12/2023 13:30 PM
Client Agency:		
Contact Person: Ma. Luisa C Tenedero Chairperson, Bids and Awards Committee BWD Compound, Utility Road Baguio City Benguet Philippines 2600 63-74-4424858 63-74-4424858 purchasing.bwd2014@gmail.com		

Description

500 pieces ½" Ball Valve / Stop Cock Ball Type-Lock Wing (Threaded)
(Please see complete specifications below.)
Approved Budget Cost: ₱580.00/PC

10 pieces 1" Ball Valve / Stop Cock Ball Type-Lock Wing (Threaded)
(Please see complete specifications below.)
Approved Budget Cost: ₱1,138.00 / pc

15 pieces 1" Check Valve, Class 125 Screwed Cap, swing type disc, Threaded ends, WOG, Non-Shock, 1.38 MPa (200 psi), Saturated steam pressure (SSP), 0.86 MPa (125 psi)
Materials:
Body: bronze or brass; Cap: brass or bronze;
Hinge pin: brass or stainless steel; Disc: brass
Approved Budget Cost: ₱720.00 / pc

18 pieces 1 1/2" Check Valve, Class 125 Screwed Cap, swing type disc, Threaded ends, WOG, Non-Shock, 1.38 MPa (200 psi); Saturated steam pressure (SSP), 0.86 MPa (125 psi)
Materials:
Body: bronze or brass; Cap: brass or bronze;
Hinge pin: brass / stainless steel; Disc: brass
Approved Budget Cost: ₱2,225.00 / pc

345 pieces, 1" Ø Gate Valve, Threaded Type Class 125
(please see complete specifications below.)
Approved Budget Cost: ₱846.00 / pc

10 pieces 1 ½" Ø Gate Valve, Threaded Type Class 125
(please see complete specifications below.)
Approved Budget Cost: ₱1,714.00 / pc

5 pieces, 2" Ø Gate Valve, Threaded Type Class 125
(please see complete specifications below.)
Approved Budget Cost: ₱2,642.00 / pc

16 pieces, 2" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts
(please see complete specifications below.)
Approved Budget Cost: ₱11,600.00 /PC

16 pieces 4" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts
(please see complete specifications below.)
Approved Budget Cost: ₱22,075.00 /PC

10 pieces 4" Ø Gate Valve, flanged type with companion steel flanges and BNG
(please see complete specifications below.)
Approved Budget Cost: ₱30,665.00 / pc

6 pieces 6" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts
(please see complete specifications below.)
Approved Budget Cost: ₱38,945.00 / pc

8 pieces 8" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts
(please see complete specifications below.)
Approved Budget Cost: ₱54,570.00 / pc

140 pieces ½" Ø HDPE Coupling
Body: Polypropylene, high grade copolymer
Split Ring: Acetal; Liner: Acetal, O-ring fixed inside;
Seal: Nitrile Rubber NBR
Approved Budget Cost: ₱246.00 / pc

13 pieces ¾" Ø HDPE Coupling
Body: Polypropylene, high grade copolymer
Split Ring: Acetal; Liner: Acetal, O-ring fixed inside;
Seal: Nitrile Rubber NBR
Approved Budget Cost: ₱207.50 / pc

100 pieces 1" Ø HDPE Coupling
Body: Polypropylene, high grade copolymer
Split Ring: Acetal; Liner: Acetal, O-ring fixed inside;
Seal: Nitrile Rubber NBR
Approved Budget Cost: ₱372.00 / pc

500 pieces ½" Ø HDPE Male Coupling Adapter
Body: Polypropylene, high-grade copolymer
Split Ring: Acetal; Liner: Acetal, o-ring fixed inside;
Seal: Nitrile Rubber NBR
Approved Budget Cost: ₱186.00 / pc

170 pieces ¾" Ø HDPE Male Coupling Adapter
Body: Polypropylene, high-grade copolymer
Split Ring: Acetal; Liner: Acetal, o-ring fixed inside;
Seal: Nitrile Rubber NBR
Approved Budget Cost: ₱132.00 / pc

240 pieces 1" Ø HDPE Male Coupling Adapter
Body: Polypropylene, high grade copolymer
Split Ring: Acetal; Liner: Acetal, o-ring fixed inside;
Seal: Nitrile Rubber NBR
Approved Budget Cost: ₱148.00 / pc

250 pieces 1" Ø Poly BST Elbow "Plasson"
Body: Polypropylene, High Grade Copolymer Split Ring:
Acetal; Seal: Nitrile Rubber (NBR)
Approved Budget Cost: ₱291.80 / pc

210 pieces 2" x 1" Tapping Saddle

(please see complete specifications below)
Approved Budget Cost: ₱ 4,196.00 / pc

65 pieces 3" x 1" Tapping Saddle
(please see complete specifications below)
Approved Budget Cost: ₱ 4,496.00 / pc

143 pieces 4" x 1" Tapping Saddle
(please see complete specifications below)
Approved Budget Cost: ₱4,564.00 / pc

33 pieces 6" x 1" Tapping Saddle
(please see complete specifications below)
Approved Budget Cost: ₱5,844.00 / pc

8 pieces Universal Tapper 8" x 1" (for PVC)
(please see complete specifications below)
Approved Budget Cost: ₱14,762.00 / pc

10 pieces Universal Tapper 10" x 1" (for PVC)
(please see complete specifications below)
Approved Budget Cost: ₱15,380.00 / pc

5 pieces Universal Tapper 12" x 1" (for PVC)
(please see complete specifications below)
Approved Budget Cost: ₱15,708.00 / pc

x x x x

BALL VALVE SPECIFICATIONS:

-Elements of the valve should be free from dirt, and there should not be any dirt, chip, burrs, and flakes etc. before assembling.

-The threaded parts of the socket should be coated with sealing glue.

-The valve should not present block to the circulation of closing and opening, and it should be flexible.

-When the valve is fully open, the degree of the body axis and ball axis should be less than 3 degrees.

-Seal test should be carried and testing pressure should not be less than 0.6Mpa.

-The valve should be turned off during delivery.

Materials

Body: CW617N; Bonnet: CW617N

Ball: Hpb57-3; Ball Seat: PTFE SM031

Stem: Hpb57-3; Handle: Hpb57-3

Elastic Cylindrical Pin: Stainless Steel

GATE VALVE (THREADED) SPECIFICATIONS:

Features: Brass Body, Non-Rising stem, Screw-over bonnet, Threaded ends

Specifications:

Nominal pressure: Non-shock working pressure

Max working pressure 150 psi

Fitting to withstand min. working pressure of 1.00 Thread shall be NPT

Water way shall unobstructed when fully opened

Material List

Handwheel: Alloy / Packing Nut: Brass

Bonnet: Brass / Stem: Brass Rod

Wedge: Brass / Body: Brass

Bonnet Gasket: Plastic / Packing: Teflon

GATE VALVE FLANGED TYPE SPECIFICATIONS:

Design Code: Hydraulic test to BS 5163 (DIN3230 / DIN3352) or JIS B2043, DIN 3352, AWWA C509, BS5163

Maximum Pressure: PN16 or 16 bar

Temperature Range: -20 to 160 degrees centigrade

Face to Face: BS 5163 or JIS B2002, DIN 3202-F5, DIN 3202-F4, ANSI B16.10, BS 5163

End Flange: EN1092-2 (ISO 7005-2) or JIS B2212 10K, DIN 2533 PN 10/16, ANSI 150#, BS4504 PN 10/16

Tightness Test: Operating Torque Test or JIS B2003, DIN 3230, AWWA C509, BS 6755

Materials:

Body: Ductile Iron, GGG-50 to DIN 1693 (BS 2789 grade 500-7) or Ductile Iron

Wedge: Ductile Iron (DI) + NBR or Ductile Iron, GGG-50, core fully encapsulated with EPDM rubber with integral wedge nut of dezincification resistant brass, CZ 132 to BS 2874

Wedge Nut: Brass or Dezincification Resistant Brass

Stem: Stainless Steel, DIN X 20 Cr 13 or Stainless Steel / Brass

Bonnet Gasket: EPDM Rubber or EPDM / NBR

Bonnet: Ductile Iron (DI) or Stainless Steel A2, sealed with hot melt

O-Ring: NBR or EPDM / NBR

Stem Collar: Brass

Gland Flange: Ductile Iron or Ductile Iron GJS-500-7 (GGG-50)

Dustproof Ring: NBR or EPDM / NBR

Hex Nut: Cast Iron

Overall Dimensions:

Size / DN Length (L) mm Height (H) mm Width or D mm Weight kgs

DN50 (2") 178 300-241 160-165 13-14

DN100 (4") 229 334-430 200-220 26-28

DN150 (6") 267 448-565 260-285 51-52

DN200 (8") 292 62-680 320-340 77-83

TAPPING SADDLE SPECIFICATIONS:

Body: Polypropylene, high grade copolymer

Nuts: Polypropylene, high grade copolymer

Split Ring: Acetal (POM); Seal: EPDM; Without bolts and nuts, filled with self-boring mechanism

made of brass that will function as a valve; O-Ring of outlet fixed inside the body. Threads must conform to ISO - 7/1, BS21 - 1973, DIN 2999, NEN 3258, AS 1722 part. 1- 1975. Quality conforms to ISO-9002.

UNIVERSAL TAPPER SPECIFICATIONS

For all kinds of pipes and sizes except PE Pipe Tapping on PA adaptor internally threaded.

Threading to BSP 1/2", 3/4" and 1" use for water and neutral liquids to max. 70°C.

Maximum working pressure: 16 bar

Materials: Saddle upper part: Ductile Iron, GGG5- to DIN 1693 (BS2789 grade 500-7) with rubber liner; Stirrup (lower part): Stainless Steel A2;

Coating: Electro Statically applied epoxy resin to DIN 30677 - Internally and externally: Stirrup bushing: Stainless Steel 303, Adaptor: Polyamide PA 11GF; Rubber

Gasket: NBR; Rubber Lining: NBR Bolts: Stainless Steel A2;

Washer: Stainless Steel A2; Support Washer: PE: HD

Option:

Bolt/washer Stainless Steel A4; Adaptor: Blank (no hole), Stirrup (Lower part) other: rand size / 100mm band width

Note: not to be awarded on a one (1) lot basis.

xx xx xx xx

This is a two (2) envelope system:

Envelope "A" to contain the following, among others:

a) A refundable bid bond in the form of cash, Manager's or Cashier's check equivalent to 2% or a surety bond callable on demand issued by a surety or insurance company duly certified by the Insurance Commission equivalent to 5% of the total approved budget cost is required for a total purchase bid amount of ₱ 50,000.00 and above. Validity of the surety bond is 120 days from the date of opening of bids OR Bid Securing Declaration regardless of the amount of bid;

b) Terms of payment, delivery, warranty, bid validity, and complete specifications;

c) Brochure/s (Original);

d) Proof of payment of a non-refundable fee of ₱5,000.00; otherwise, bids shall not be opened

e) Certificate of Authorized Distributorship / Dealership issued by the Principal Supplier to the participating bidder (with red ribbon) if none has been submitted to the BAC in its Accreditation;

-For bidders who have principal foreign suppliers, the BWD-BAC shall accept an Apostilled Certificate of Authorized Distributorship / Dealership issued by a competent authority of the host government in lieu of the Certificate of Authorized Distributorship / Dealership (with red ribbon), except for non-contracting countries to the Apostille Convention, which still require the red ribbon requirement.

-For locally produced/manufactured products, only a certificate of Authorized Distributorship / Dealership w/o red ribbon is required if applicable;

f) ISO Certificate issued to the principal supplier/participating bidder for the offered material or equipment brand name (if none has been submitted to the BAC in its Accreditation);

g) International Certificate of Warranty.

Envelope "B" to contain the bid cost per unit.



Pre-bid Conference

Date	Time	Venue
24/11/2023	9:30:00 AM	Pre-bid conference: November 24, 2023 9:30am via Zoom Application Meeting ID: 452 718 8447 Password: 9Buvqr

Created by Ma. Luisa C Tenedero

Date Created 09/11/2023

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.

 	BAGUIO WATER DISTRICT BWD Compound, Utility Road, Baguio City 2600	Document No.	ADM-PUR-F003
	REQUEST FOR BIDS/QUOTATION (RQ)	Revision Date	February 15, 2020
		Revision No.	01

To: _____

 (Name of Supplier)

Contact Person: _____
Address: _____


Contact no.: _____

RQ No.: 10 – 192P-B
PR / JO No.: 192P
Date of RQ: October 31, 2023
Purpose of RQ:
 4th Quarter Consolidated Supplies
 and Materials

NOTE: DATA REQUIRED MUST BE FILLED UP COMPLETELY. FAILURE TO INDICATE THE PRICE VALIDITY, TERMS, WARRANTY PERIOD AND DELIVERY PERIOD SHALL MEAN OUTRIGHT DISQUALIFICATION OF BIDS

	Qty.	Description	U-Price	Total
VALIDITY DATE: _____ day (30 days minimum)	500 pieces	1/2" Ball Valve / Stop Cock Ball Type-Lock Wing (Threaded) (please see complete specifications below) Approved Budget Cost: ₱580.00 / pc		
DELIVERY: _____ working days _____ calendar days _____ FOB warehouse	10 pieces	1" Ball Valve / Stop Cock Ball Type-Lock Wing (Threaded) (please see complete specifications below) Approved Budget Cost: ₱1,138.00 / pc		
WARRANTY _____ calendar days upon acceptance.	15 pieces	1" Check Valve, Class 125 Screwed Cap, swing type disc, Threaded ends, WOG, Non-Shock, 1.38Mpa (200 psi), Saturated steam pressure (SSP), 0.86Mpa (125 psi) Materials: Body: bronze / brass; Cap: brass / bronze; Hinge pin: brass / stainless steel; Disc: brass Approved Budget Cost: ₱720.00 / pc		
TERMS:	18 pieces	1 1/2" Check Valve, Class 125 Screwed Cap, swing type disc, Threaded ends, WOG, Non-Shock, 1.38Mpa (200 psi), Saturated steam pressure (SSP), 0.86Mpa (125 psi) Materials: Body: bronze / brass; Cap: brass / bronze; Hinge pin: brass / stainless steel; Disc: brass Approved Budget Cost: ₱2,225.00 / pc		
	345 pieces	1" Ø Gate Valve, Threaded Type Class 125 (please see complete specifications below) Approved Budget Cost: ₱846.00 / pc		





December 06, 2023



BAGUIO WATER DISTRICT
BWD Compound, Utility Road, Baguio City 2600




Document No.	ADM-PUR-F003
Revision Date	February 15, 2020
Revision No.	01

REQUEST FOR BIDS/QUOTATION (RQ)

10 pieces	1 ½" Ø Gate Valve, Threaded Type Class 125 (please see complete specifications below) Approved Budget Cost: ₱1,714.00 / pc		
5 pieces	2" Ø Gate Valve, Threaded Type Class 125 (please see complete specifications below) Approved Budget Cost: ₱2,642.00 / pc		
8 pieces	2" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts (please see complete specifications below) Approved Budget Cost: ₱11,600.00 / pc		
16 pieces	4" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts (please see complete specifications below) Approved Budget Cost: ₱22,075.00 / pc		
10 pieces	4" Ø Gate Valve, flanged type with companion steel flanges and BNG (please see complete specifications below) Approved Budget Cost: ₱30,665.00 / pc		
6 pieces	6" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts (please see complete specifications below) Approved Budget Cost: ₱38,945.00 / pc		
8 pieces	8" Ø Gate Valve, flanged type with combination flanges and sealing ring and bolts & nuts (please see complete specifications below) Approved Budget Cost: ₱54,570.00 / pc		
140 pieces	½" Ø HDPE Coupling Body: Polypropylene, high grade copolymer Split Ring: Acetal; Liner: Acetal, O-ring fixed inside; Seal: Nitrile Rubber NBR Approved Budget Cost: ₱246.00 / pc		
13 pieces	¾" Ø HDPE Coupling Body: Polypropylene, high grade copolymer Split Ring: Acetal; Liner: Acetal, O-ring fixed inside; Seal: Nitrile Rubber NBR Approved Budget Cost: ₱207.50 / pc		

Signature

Signature
December 06, 2023

  	BAGUIO WATER DISTRICT		Document No.	ADM-PUR-F003
	BWD Compound, Utility Road, Baguio City 2600		Revision Date	February 15, 2020
	REQUEST FOR BIDS/QUOTATION (RQ)		Revision No.	01

100 pieces	1" Ø HDPE Coupling Body: Polypropylene, high grade copolymer Split Ring: Acetal; Liner: Acetal, O-ring fixed inside; Seal: Nitrile Rubber NBR Approved Budget Cost: ₱372.00 / pc		
500 pieces	½" Ø HDPE Male Coupling Adapter Body: Polypropylene, high grade copolymer Split Ring: Acetal; Liner: Acetal, o-ring fixed inside; Seal: Nitrile Rubber NBR Approved Budget Cost: ₱186.00 / pc		
170 pieces	¾" Ø HDPE Male Coupling Adapter Body: Polypropylene, high grade copolymer Split Ring: Acetal; Liner: Acetal, o-ring fixed inside; Seal: Nitrile Rubber NBR Approved Budget Cost: ₱132.00 / pc		
240 pieces	1" Ø HDPE Male Coupling Adapter Body: Polypropylene, high grade copolymer Split Ring: Acetal; Liner: Acetal, o-ring fixed inside; Seal: Nitrile Rubber NBR Approved Budget Cost: ₱148.00 / pc		
250 pieces	1" Ø Poly BST Elbow "Plasson" Body: Polypropylene, High Grade Copolymer Split Ring: Acetal; Seal: Nitrile Rubber (NBR) Approved Budget Cost: ₱291.80 / pc		
210 pieces	2" x 1" Tapping Saddle (please see complete specifications below) Approved Budget Cost: ₱ 4,196.00 / pc		
65 pieces	3" x 1" Tapping Saddle (please see complete specifications below) Approved Budget Cost: ₱ 4,496.00 / pc		
143 pieces	4" x 1" Tapping Saddle (please see complete specifications below) Approved Budget Cost: ₱4,564.00 / pc		
33 pieces	6" x 1" Tapping Saddle (please see complete specifications below) Approved Budget Cost: ₱5,844.00 / pc		

Smr Ray Jayw

Richard
December 06, 2023



BAGUIO WATER DISTRICT
BWD Compound, Utility Road, Baguio City 2600

Document No. ADM-PUR-F003

Revision Date February 15, 2020

Revision No. 01

REQUEST FOR BIDS/QUOTATION (RQ)

8 pieces Universal Tapper 8" x 1" (for PVC)
(please see complete specifications below)
Approved Budget Cost: ₱14,762.00 / pc

10 pieces Universal Tapper 10" x 1" (for PVC)
(please see complete specifications below)
Approved Budget Cost: ₱15,380.00 / pc

5 pieces Universal Tapper 12" x 1" (for PVC)
(please see complete specifications below)
Approved Budget Cost: ₱15,708.00 / pc

X X X X X

BALL VALVE SPECIFICATIONS:

-Elements of the valve should be free from dirt, and there should not be any dirt, chip, burrs, and flakes etc. before assembling.

-The threaded parts of the socket should be coated with sealing glue.

-The valve should not present block to the circulation of closing and opening, and it should be flexible.

-When the valve is fully open, the degree of the body axis and ball axis should be less than 3 degrees.

-Seal test should be carried and testing pressure should not be less than 0.6Mpa.

-The valve should be turned off during delivery.

Materials

Body: CW617N; Bonnet: CW617N

Ball: Hpb57-3; Ball Seat: PTFE SM031

Stem: Hpb57-3; Handle: Hpb57-3

Elastic Cylindrical Pin: Stainless Steel

GATE VALVE (THREADED) SPECIFICATIONS:

Features: Brass Body, Non-Rising stem, Screw-over bonnet,

Threaded ends

Specifications:

Nominal pressure: Non-shock working pressure

Max working pressure 150 psi

Fitting to withstand min. working pressure of 1.00

Thread shall be NPT

Water way shall unobstructed when fully opened

Material List

Handwheel: Alloy / Packing Nut: Brass

Smr Ray Sayw

Michael
December 06, 2023



BAGUIO WATER DISTRICT
BWD Compound, Utility Road, Baguio City 2600

Document No.	ADM-PUR-F003
Revision Date	February 15, 2020
Revision No.	01

REQUEST FOR BIDS/QUOTATION (RQ)

Bonnet: Brass / Stem: Brass Rod
Wedge: Brass / Body: Brass
Bonnet Gasket: Plastic / Packing: Teflon

GATE VALVE FLANGED TYPE SPECIFICATIONS:

Design Code: Hydraulic test to BS 5163 (DIN3230 / DIN3352) or JIS B2043, DIN 3352, AWWA C509, BS5163
Maximum Pressure: PN16 or 16 bar
Temperature Range: -20 to 160 degrees centigrade
Face to Face: BS 5163 or JIS B2002, DIN 3202-F5, DIN 3202-F4, ANSI B16.10, BS 5163
End Flange: EN1092-2 (ISO 7005-2) or JIS B2212 10K, DIN 2533 PN 10/16, ANSI 150#, BS4504 PN 10/16
Tightness Test: Operating Torque Test or JIS B2003, DIN 3230, AWWA C509, BS 6755

Materials:

Body: Ductile Iron, GGG-50 to DIN 1693 (BS 2789 grade 500-7) or Ductile Iron
Wedge: Ductile Iron (DI) + NBR or Ductile Iron, GGG-50, core fully encapsulated with EPDM rubber with integral wedge nut of dezincification resistant brass, CZ 132 to BS 2874

Wedge Nut: Brass or Dezincification Resistant Brass

Stem: Stainless Steel, DIN X 20 Cr 13 or Stainless Steel / Brass

Bonnet Gasket: EPDM Rubber or EPDM / NBR

Bonnet: Ductile Iron (DI) or Stainless Steel A2, sealed with hot melt

O-Ring: NBR or EPDM / NBR

Stem Collar: Brass

Gland Flange: Ductile Iron or Ductile Iron GJS-500-7 (GGG-50)

Dustproof Ring: NBR or EPDM / NBR

Handwheel: Ductile Iron (DI)

Hex Nut: Cast Iron

Overall Dimensions:

Size / DN	Length (L) mm	Height (H) mm	Width or D mm	Weight kgs
DN50 (2")	178	300-241	160-165	13-14
DN100 (4")	229	334-430	200-220	26-28
DN150 (6")	267	448-565	260-285	51-52
DN200 (8")	292	62-680	320-340	77-83

TAPPING SADDLE SPECIFICATIONS:

Body: Polypropylene, high grade copolymer

Nuts: Polypropylene, high grade copolymer

Snar
for Jay W

Michael
December 06, 2023



BAGUIO WATER DISTRICT
BWD Compound, Utility Road, Baguio City 2600

Document No.	ADM-PUR-F003
Revision Date	February 15, 2020
Revision No.	01

REQUEST FOR BIDS/QUOTATION (RQ)

Split Ring: Acetal (POM); Seal: EPDM;
Without bolts and nuts, filled with self-boring mechanism made of brass that will function as a valve; O-Ring of outlet fixed inside the body. Threads must conform to ISO – 7/1, BS21 – 1973, DIN 2999, NEN 3258, AS 1722 part. 1-1975. Quality conforms to ISO-9002.

UNIVERSAL TAPPER SPECIFICATIONS

For all kinds of pipes and sizes except PE Pipe

Tapping on PA adaptor internally threaded.

Threading to BSP 1/2", 3/4" and 1"

use for water and neutral liquids to max. 70°C.

Maximum working pressure: 16 bar

Materials: Saddle upper part: Ductile Iron, GGG5- to DIN 1693 (BS2789 grade 500-7)

with rubber liner; Stirrup (lower part): Stainless Steel A2;

Coating: Electro Statically applied epoxy resin to DIN

30677 – Internally and externally: Stirrup bushing:

Stainless Steel 303, Adaptor: Polyamide PA 11GF; Rubber

Gasket: NBR; Rubber Lining: NBR Bolts: Stainless Steel A2;

Washer: Stainless Steel A2; Support Washer: PE: HD

Option:

Bolt/washer Stainless Steel A4; Adaptor: Blank (no hole),

Stirrup (Lower part) other: rand size / 100mm band width




Note: not to be awarded on a one (1) lot basis.

This is a two (2) envelope system:

Envelope "A" to contain the following, among others:




- A refundable bid bond in the form of cash, Manager's or Cashier's check equivalent to 2% or a surety bond callable on demand issued by a surety or insurance company duly certified by the Insurance Commission equivalent to 5% of the total approved budget cost is required for a total purchase bid amount of ₱50,000.00 and above. Validity of the surety bond is 120 days from the date of opening of bids OR Bid Securing Declaration regardless of the amount of bid;
- Terms of payment, delivery, warranty, bid validity, and complete specifications;
- Brochure/s (Original);
- Proof of payment of a non-refundable fee of **₱5,000.00**; otherwise, bids shall not be opened
- Certificate of Authorized Distributorship / Dealership



  	BAGUIO WATER DISTRICT BWD Compound, Utility Road, Baguio City 2600		Document No.	ADM-PUR-F003
	REQUEST FOR BIDS/QUOTATION (RQ)		Revision Date	February 15, 2020
			Revision No.	01
<p>issued by the Principal Supplier to the participating bidder (with red ribbon) if none has been submitted to the BAC in its Accreditation;</p> <p>-For bidders who have principal foreign suppliers, the BWD-BAC shall accept an Apostilled Certificate of Authorized Distributorship / Dealership issued by a competent authority of the host government in lieu of the Certificate of Authorized Distributorship / Dealership (with red ribbon), except for non-contracting countries to the Apostille Convention, which still require the red ribbon requirement.</p> <p>-For locally produced/manufactured products, only a certificate of Authorized Distributorship / Dealership w/o red ribbon is required if applicable;</p> <p>f) ISO Certificate issued to the principal supplier/participating bidder for the offered material or equipment brand name (if none has been submitted to the BAC in its Accreditation);</p> <p>g) International Certificate of Warranty.</p> <p>Envelope "B" to contain the bid cost per unit.</p> <p>Pre-bid conference: November 24, 2023 9:30am via Zoom Application Meeting ID: 452 718 8447 Password: 9Buvqr</p>				

By: Supplier or Authorized Representative: _____ (sign over printed name)

Deadline of submission of bids: December 06, 2023 Opening of bids: 1:30 pm

Prepared by:  **M. Lamangan** Noted by:  **ATTY. M.A. LUISA C. TENEDERO**  **ENGR. REYNALDO C. JAYCO**

PURCHASING BAC IN-HOUSE BAC-TECHNICAL

BWD RESERVES THE RIGHT TO REJECT BIDS &/OR DECLARE A FAILURE OF BIDDING
PURSUANT TO THE PERTINENT PROVISIONS OF RA 9184

Telefax No. (074) 442-4858 (Purchasing) / 444-7246