

Central Portal for Philippine Government Procurement Oppurtunities

Bid Notice Abstract

Invitation to Bid (ITB)

Reference Number

10337598

Procuring Entity

BAGUIO WATER DISTRICT - BAGUIO CITY

Title

1 Lot Submersible Pump and Motor with Variable Frequency Drive

Area of Delivery

Benguet

Solicitation Number:	11-174P-E	Status	Pending
Trade Agreement:	Implementing Rules and Regulations		
Procurement Mode:	Public Bidding	Associated Components	1
Classification:	Goods		
Category:	Industrial pumps and compressors	Bid Supplements	0
Approved Budget for the Contract:	PHP 1,050,000.00		
Delivery Period:		Document Request List	0
Client Agency:			
Contact Person:	Ma. Luisa C Tenedero Chairperson, Bids and Awards Committee	Date Published	21/11/2023
	BWD Compound, Utility Road Baguio City Benguet	Last Updated / Time	20/11/2023 09:19 AM
	Philippines 2600 63-74-4424858 63-74-4424858	Closing Date / Time	18/12/2023 13:30 PM

Description

1 LOT Submersible motor with the following specifications:

purchasing.bwd2014@gmail.com

I. General Requirements:

Rating: 30 Hp

Nominal Voltage: 460 V Frequency: 60 Hz

Standard Diameter: 6 - 8 Inches

Lead Wire or Cables: Plug-in or Detachable

Rotor Spline: NEMA Standard Nominal Speed: 3600 rpm

Number of Phase: 3

II. Material Components: End Castings : Gray Iron Stator Shell: 301 SS

Stator Ends: Low Carbon Steel

Shaft Extension: 303 SS (5-30HP) 17-4 SS (40-60HP)

Fasteners: 300 and 400 Series SS Seal Cover: 304 SS and Sintered Bronze

Seal: Carbon Ceramic Face

Diaphragm: Nitrile

Diaphragm Plate: 304,SS Diaphragm Spring: 302 SS

Slinger: Nitrile

Lead Wire (or Cable): XLPE 125°C

Lead Potting : Epoxy

Lead Jam Nut : 300 Series SS Filter : Delrin and Polyester

III. Must Submit authenticated Certificate of dealership or distributorship with red ribbon

IV. ISO Certified

Coupled to: Submersible Turbine Pump, all stainless construction

I. General Requirements:

Capacity: 150 gpm

TDH: 475 ft

Eff. @ Rated Capacity: 70 % Speed (nominal): 3600 rpm Std. Dia.: Not more than 6 inches

Check Valve and Strainer: Built-in: Capable to handle sand content from 50 to 150 ppm

on certain pump sizes

Coupling: Spline type in NEMA standard.

III. Others

Discharge Nipple : 4" Ø x 12" S-40, BI or SS Discharge Coupling : 4" Ø S-80, BI or SS

IV. Must submit an authenticated certificate of Dealership / Distributorship with Red Ribbon.

V. ISO Certified

(Please refer to attached for complete specifications.)

With Variable Frequency Drive Adaptable to 50 hp

Voltage Rating: 460V Supply Freq.: 60Hz No. of Phase: 3

Capacity of pressure transmitter: 0-25 bars

Standard Specifications for Variable Frequency Drive

1 MAIN SUPPLY (L1, L2, L3)

Supply Voltage 3 x 380-480V AC

or as specified by

end-user

Supply Frequency 60 Hz

Displacement Power Factor > 0.98

True Power Factor 0.9

Switching on Input Supply L1,

L2, L3

1 - 2 times /

minute

2 OUTPUT DATA (U, V, W)

Output Voltage 0 - 100%

Switching on Output Unlimited

Ramp Times 0.1 - 3600

seconds

Maximum Output Frequency 590 Hz

3 DIGITAL INPUTS

Programmable Digital Inputs 6

Logic PNP

Voltage Level 0 - 24V DC

4 ANALOGUE INPUTS

Number of Analogue Inputs 2

Modes Current

Voltage Level - 10 to +10

(scaleable)

Current Level 0/4 to 20mA

(scaleable)

5 PULSE INPUTS

Programmable Pulse Inputs 2

Voltage Level 0-24V DC (PNP

positive logic)

Pulse Input Accuracy Max. error: 0.1% of

full scale

6 ANALOGUE OUTPUT

Programmable Analogue

Outputs

Current Range at Analogue

Output

0-4 - 20mA

7 RELAY OUTPUTS

Programmable Relay Outputs 2

8 FIELDBUS COMMUNICATION Ethernet IP 9 AMBIENT TEMPERATURE: Up to 55°C

10 HARDWARE SPECIFICATIONS IP 55 Enclosure

11 OTHER ACCESSORIES Pressure Transmitter 25 Bars

Approved Budget Cost: ₱1,050,000.00 / lot

XXXXX

This is a two (2) envelope system:

Envelope "A" to contain the following, among others:

- a) A refundable bid bond in the form of cash, a manager's or cashier's check equivalent to 2%, or a surety bond callable on demand issued by a surety or insurance company duly certified by the Insurance Commission equivalent to 5% of the total approved budget cost is required for a total purchase bid amount of ₱ 50,000.00 and above. The validity of the surety bond is 120 days from the date of opening of bids OR Bid Securing declaration, regardless of the amount of bid.
- b) Terms of payment, delivery, warranty, bid validity, and complete specifications;

c) Brochure(s) (Original):

d) Proof of payment of a non-refundable fee of \$5,000.00; otherwise, bids shall not be opened

e) Certificate of Authorized Distributorship / Dealership issued by the Principal Supplier to the participating bidder (with red ribbon) if none has been submitted to the BAC in its Accreditation;

-For bidders who have principal foreign suppliers, the BWD-BAC shall accept an Apostilled Certificate of Authorized Distributorship or Dealership issued by a competent authority of the host government in lieu of the Certificate of Authorized Distributorship / Dealership (with red ribbon), except for non-contracting countries to the Apostille Convention, which still require the red ribbon requirement.

-For locally produced or manufactured products, only a certificate of Authorized Distributorship or Dealership without a red ribbon is required, if applicable.

f) ISO Certificate issued to the principal supplier or participating bidder for the offered material or equipment brand name (if none has been submitted to the BAC in its Accreditation);

g) International Certificate of Warranty

Envelope "B" to contain the bid cost per unit.

Pre-bid conference: December 4, 2023

9:30am via Zoom Application Meeting ID: 452 718 8447

Password: 9Buvgr **Pre-bid Conference**

04/12/2023

9:30:00 AM

Pre-bid conference: December 4, 2023

9:30am via Zoom Application Meeting ID: 452 718 8447

Password: 9Buvqr

Created by

Ma. Luisa C Tenedero

Date Created

20/11/2023

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.

© 2004-2023 DBM Procurement Service. All rights reserved.

Help | Contact Us | Sitemap



Document No. ADM-PUR-F003 Revision Date October 29, 2019

02

Revision No.

REQUEST FOR BIDS/QUOTATION (RQ)

То:		RQ No.:	11 – 174P-E
	(Name of Supplier)	PR / JO No.:	174P
Contact Person:		Date of RQ:	November 8, 2023
Address:	_	Purpose of RQ:	
		Proposed Gibra	altar DW2
Contact no.:		Commissiong:	
		Item B: Electro-	mechanical System

NOTE: DA	TA REQU	IRED MUST BE FILLED (JP (COMPLETELY. FAILURE TO IN	DICATE THE	
P				PERIOD AND DELIVERY PERI	OD	
				QUALIFICATION OF BIDS		
	Qty.		Des	cription	U-Price	Total
VALIDITY DATE:	1 lot	Submersible Motor with the following specifications:				
(30 days minimum)		I. General Requireme	nts:	30 Hp		
DELIVERY:		Nominal Voltage Frequency		460 V 60 Hz		
working days calendar days FOB warehouse		Standard Diameter Lead Wire / Cables Rotor Spline	:	6 – 8 Inches Plug-in or Detachable NEMA Standard		
WARRANTY		Nominal Speed Number of Phase		3600 rpm		
		II. Material Compone	•	•		
calendar days upon acceptance.		End Castings Stator Shell	:	Gray Iron 301 SS		
TERMS:		Stator Ends Shaft Extension		Low Carbon Steel 303 SS (5-30HP) 17-4 SS (40-60HP)		
		Fasteners Seal Cover Seal	:	300 & 400 Series SS 304 SS & Sintered Bronze Carbon Ceramic Face		
		Diaphragm Diaphragm Plate		Nitrile 304 SS		
		Diaphragm Spring Slinger Lead Wire (or Cable)	:	302 SS Nitrile XLPE 125°C		
		Lead Potting Lead Jam Nut	:	Epoxy 300 Series SS		
		Filter	:	Delrin & Polyester		
III. Must Submit authenticated Certificate of dealership / distributorship with red ribbon IV. ISO Certified		1				
						0

Smi

Page 1 of 4 of RQ 11 – 174P-E dated November 8, 2023

December 18, 2023



Document No. ADM-PUR-F003

Revision Date October 29, 2019

Revision No. 02

REQUEST FOR BIDS/QUOTATION (RQ)

Coupled to: Submersible Turbine Pump, all stainless construction

I. General Requirements:

Capacity : 150 gpm
TDH : 475 ft
Eff. @ Rated Capacity : 70 %
Speed (Nominal) : 3600 rpm

Std. Dia. : Not more than 6 inches

Check Valve and Strainer: Built-in

- Capable to handle sand content from 50 to 150ppm

on certain pump sizes

Coupling : Spline type in NEMA std.

III. Others

Discharge Nipple : 4" Ø x 12" S-40, BI or SS

Discharge Coupling : 4" Ø S-80, BI or SS

IV. Must submit Authenticated Certificate of Dealership / Distributorship with Red Ribbon

V. ISO Certified

(Please refer to attached for complete

specifications)

with Variable Frequency Drive

Adaptable to 50hp Voltage Rating: 460V Supply Freq.: 60Hz No. of Phase: 3

Capacity of pressure transmitter: 0-25 bars

Standard Specifications for Variable Frequency Drive

1 **MAIN SUPPLY (L1, L2, L3)**

Supply Voltage 3 x 380-480V AC

or as specified by

end-user

Supply Frequency 60 Hz
Displacement Power Factor > 0.98
True Power Factor 0.9

Switching on Input Supply L1, 1-2 times /

L2, L3 minute

2 OUTPUT DATA (U, V, W)

Output Voltage 0 - 100% Switching on Output Unlimited Ramp Times 0.1 - 3600

seconds

Maximum Output Frequency 590 Hz

Smi Jayw

Page 2 of 4 of RQ 11 – 174P-E dated November 8, 2023

December 18, 2023



Document No. ADM-PUR-F003

REQUEST FOR BIDS/QUOTATION (RQ)

Revision Date October 29, 2019 Revision No. 02

3 **DIGITAL INPUTS**

Programmable Digital Inputs PNP Logic

Voltage Level 0 - 24V DC

4 ANALOGUE INPUTS

Number of Analogue Inputs 2

Modes Current Voltage Level - 10 to +10

(scaleable)

Current Level 0/4 to 20mA

(scaleable)

5 PULSE INPUTS

Programmable Pulse Inputs

Voltage Level 0-24V DC (PNP

positive logic)

Max. error: 0.1% of Pulse Input Accuracy

full scale

6 ANALOGUE OUTPUT

Programmable Analogue

Outputs

Current Range at Analogue 0-4 - 20mA

Output

7 RELAY OUTPUTS

Programmable Relay Outputs

8 FIELDBUS COMMUNICATION Ethernet IP

9 AMBIENT TEMPERATURE

Up to 55°C

10 HARDWARE SPECIFICATIONS IP 55 Enclosure

11 **OTHER ACCESSORIES**

Pressure Transmitter 25 Bars

Approved Budget Cost: ₱1,050,000.00 / lot

X X X X X

This is a two (2) envelope system: Envelope "A" to contain the following; among others:

a) A refundable bid bond in the form of cash, Manager's or Cashier's check equivalent to 2% or surety bond callable on demand issued by a surety or insurance company duly certified by the Insurance Commission equivalent to 5% of the total approved budget cost is required for a total purchase bid amount of ₱ 50,000.00 and above. Validity of the surety bond is 120 days from the date of opening of bids **OR** Bid Securing Declaration regardless of amount of bid;

Page 3 of 4 of RQ 11 - 174P-E dated November 8, 2023



Document No. ADM-PUR-F003

REQUEST FOR BIDS/QUOTATION (RQ)

Revision Date October 29, 2019
Revision No. 02

b)	Terms of payment, delivery, warranty, bid validity
	and complete specifications;
	D 1 ((C : : 1)

- c) Brochure/s (Original);
- d) Proof of payment of a non-refundable fee of <u>₱5,000.00</u>; otherwise, bids shall not be opened
- e) Certificate of Authorized Distributorship /
 Dealership issued by the Principal Supplier to the
 participating bidder (with red ribbon) if none has
 been submitted to the BAC in its Accreditation;
 -For bidders who have foreign principal suppliers,
 the BWD-BAC shall accept an Apostilled Certificate
 of Authorized Distributorship / Dealership issued
 by a competent authority of the host government
 in lieu of the Certificate of Authorized
 Distributorship / Dealership (with red ribbon),
 except for non-contracting countries to the
 Apostille Convention, which still require the red
 ribbon requirement.
 - -For locally produced / manufactured products, only a certificate of Authorized Distributorship / Dealership w/o red ribbon is required if applicable;
- f) ISO Certificate issued to the principal supplier/participating bidder for the offered material or equipment brand name (if none has been submitted to the BAC in its Accreditation);
- g) International Certificate of Warranty.

Envelope "B" to contain the bid cost per unit.

Pre-bid conference: December 04, 2023

9:30am via Zoom Application Meeting ID: 452 718 8447

Password: 9Buvqr

By: Supplier or Authorized Representative:(sign	ver printed name
--	------------------

Deadline of submission of bids: December 18, 2023 Opening of bids: 1:30 pm

Prepared by: MCLAMANGAN Noted by: ATTY. MA. LUISA C. TENEDERO ENGR. REYNALDO C. JAYCO
PURCHASING BAC IN-HOUSE BAC-TECHNICAL

BWD RESERVES THE RIGHT TO REJECT BIDS &/OR DECLARE A FAILURE OF BIDDING

PURSUANT TO THE PERTINENT PROVISIONS OF RA 9184

Telefax No. (074) 442-4858 (Purchasing) / 444-7246