

BAGUIO WATER DISTRICT BWD Compound, Utility Road, Baguio City 2600

Document No.	ADM-PUR-F003
Revision Date	October 29, 2019
Revision No.	02

REQUEST FOR BIDS/QUOTATION (RQ)

Го:		RQ No.:	03 – 232P-D-R
	(Name of Supplier)	PR / JO No.:	232P
Contact Person:		Date of RQ:	March 11, 2024
Address:		Purpose of RQ:	
		For Commission	ing of Ramsey DW
Contact no.:		(ongoing drilling	ı) c/o Engr. J. B.
		Pamaylaon	
NOTE: DA	TA REQUIRED MUST BE FILLED UP COM	MPLETELY. FAILURE TO INDICA	TE THE

	RICE VAL	RED MUST BE FILLED UP COMPLETELY. FAILURE TO IND IDITY, TERMS, WARANTY PERIOD AND DELIVERY PERIONALL MEAN OUTRIGHT DISQUALIFICATION OF BIDS		
	Qty.	Description	U-Price	Total
VALIDITY DATE: day	1 unit	Soft Starter Adaptable to 125HP, 460V nominal, 3600 rpm nominal, 3 phase, 60Hz submersible motor Approved Budget Cost: ₱ 330,000.00 / unit		
30 days minimum)		* Supplier to be present during testing commissioning		
DELIVERY: working days calendar days FOB warehouse	1 unit	Variable Frequency Drive Adaptable to 100 HP, 460V, 3 phase, 60Hz submersible motor Capacity of pressure transmitter: 0-25 bars Control Body: IP 65 rated minimum		
warranty calendar days oon acceptance.		With connection-based monitoring - Motor insulation winding - Load envelope - Vibration With DC link reactors for harmonic suppression		
TERMS:		Real Time Clock battery With SEMI Certification for POWER RIDE THROUGH in the event of voltage drop. The motor will continuously run 50% @ 12 cycles * Supplier to be present during testing commissioning Approved Budget Cost: ₱ 795,000.00 / unit		
		x x x x x		
		Note: Not to be awarded on a one (1) lot basis.		
		This is a two (2) envelope system:		
		Envelope "A" to contain the following, among others:		
		a) A refundable bid bond in the form of cash, Manager's or Cashier's check equivalent to 2% or a surety bond callable on demand issued by a surety or insurance company duly certified by the Insurance Commission equivalent to 5% of the total approved budget cost is required for a total purchase bid amount of \$\P\$50,000.00 and above. Validity of the surety bond is		

April 08, 2024

Page 1 of 2 of RQ 03 – 232P-D-R dated March 11, 2024

hhul





BAGUIO WATER DISTRICT BWD Compound, Utility Road, Baguio City 2600

Document No. ADM-PUR-F003 Revision Date October 29, 2019 Revision No. 02

REQUEST FOR BIDS/QUOTATION (RQ)

120 days from the date of opening of bids OR Bid	
Securing Declaration regardless of the amount of bid;	

- Terms of payment, delivery, warranty, bid validity, and complete specifications;
- c) Brochure/s (Original);
- d) Proof of payment of a non-refundable fee of ₱5,000.00; otherwise, bids shall not be opened
- e) Certificate of Authorized Distributorship / Dealership issued by the Principal Supplier to the participating bidder (with red ribbon) if none has been submitted to the BAC in its Accreditation:
 - For bidders who have principal foreign suppliers, the BWD-BAC shall accept an Apostilled Certificate of Authorized Distributorship Dealership issued by a competent authority of the host government in lieu of the Certificate of Authorized Distributorship / Dealership (with red ribbon), except for non-contracting countries to the Apostille Convention, which still require the red ribbon requirement.
 - ii. For locally produced/manufactured products, only a certificate of Authorized Distributorship / Dealership w/o red ribbon is required if applicable;
- ISO Certificate issued to the principal supplier/participating bidder for the offered material or equipment brand name (if none has been submitted to the BAC in its Accreditation);
- International Certificate of Warranty.

Envelope "B" to contain the bid cost per unit.

Pre-bid conference: March 25, 2024

9:30am via Zoom Application Meeting ID: 452 718 8447

Password: 9Buvqr

By: Supplier or Authorized Representative:

(sign over printed name)

Deadline of submission of bids:

April 08, 2024

Opening of bids:

Prepared by: MGLamangan

Noted by: ATTY. MA TENEDERO

PURCHASING **BAC IN-HOUSE**

BWD RESERVES THE RIGHT TO REJECT BIDS &/OR DECLARE A FAILURE OF BIDDING **PURSUANT TO THE PERTINENT PROVISIONS OF RA 9184**

BWD DOES NOT ENGAGE IN SOLICITATION OF FUNDS FROM ANY INDIVIDUALS OR ENTITIES. AND WE STRONGLY ADVISE AGAINST RESPONDING TO ANY UNAUTHORIZED REQUESTS CLAIMING ASSOCIATION WITH OUR ORGANIZATION.

BAGUIO WATER DISTRICT

" Serving mankind is serving God "

PROPOSED STANDARD SPECIFICATIONS FOR SOFT STARTERS

Motor ra Motor vo Supply f	ating, Hp : bitage rating, V : frequency, Hz : of phase rpm :	Soft Starter:	
Soft Sta	arter Specifications:		
1	Main Voltage		
	L1, L2, L3	380VAC - 600VAC (+/-10%)	
2	Control Voltage		
	(A4, A6)	220-240VAC (+10%/-15%)	
	Mains Frequency	60Hz (+/-10%)	
	Rated insulation voltage to earth	600VAC	
	Rated impulse withstand voltage	4kV	
3	Short Circuit Capability		
	Coordination	Semiconductor fuses	
	Prospective current	65kA	
4	Outputs		
	Relay outputs	10A@ 250VAC resistive	
	Programmable outputs	1(NC), 1(NO), 1(CO)	
	Analogue outputs	4-20mA	
	Maximum load	600Ω (12VDC @ 20mA) accuracy +/-5%)	
	24VDC output, maximum load	200mA (accuracy +/-10%)	
5	Environmental		
	Protection	IP20 & NEMA, UL indoor type 1	
	Operating temperature	-10°C to 60°C	
	Storage temperature	-25°C to 60°C	
6	Heat Dissipation		
	During start	4.5 watts per ampere	
	Soft starter should be equipped with SCA		

TECHNICAL STANDARDS COMMITTEE:

GULLERMO V. LUCERO Vice phay person

ALLAN A. ABAD Member

EDMUND Q. LLANES Member

Recommending Approval:

FERNANDO A. PERIA Chairperson

MARCO G. DELA CRUZ, JR.

Member

RODRIGO O. DE VENECIA, JR.

ELISEO E. BRILLANTES Member

Approved by:

General Manager

BAGUIO WATER DISTRICT

" Serving mankind is serving God "

STANDARD SPECIFICATIONS FOR VARIABLE FREQUENCY DRIVE

1.	MAIN SUPPLY (L1, L2, L3) Supply Voltage	.> 0.98 \
2.	OUTPUT DATA (U, V, W) Output Voltage Switching on Output Ramp Times Maximum Output Frequency	Unlimited 0.1-3600 seconds
3.	DIGITAL INPUTS Programmable Digital Inputs Logic Voltage Level	PNP
4.	ANALOGUE INPUTS Number of Analogue Inputs Modes, Voltage Level Current Level,	Current - 10 to +10 (scaleable)
5.	PULSE INPUTS Programmable Pulse Inputs Voltage Level	0-24V DC (PNP positive logic))
6.	ANALOGUE OUTPUT Programmable Analogue Outputs,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, 1 . 0/4-20mA
7.	RELAY OUTPUTS Programmable Relay Outputs	. 2
8. 9.	FIELDBUS COMMUNICATION AMBIENT TEMPERATURE	Ethernet IP
	HARDWARE SPECIFICATIONS OTHER ACCESSORIES:	Up to 55° C IP 55 Enclosure
NOTE:	Pressure Transmitter Bidder to submit sole/exclusive distributo	Bars ership certificate.
TECHN	IICAL STANDARDS COMMITTEE:	
Vice Ch	NDO A. PERIA pairperson A. ABAD	MARCO G. DELA CRUZ, JR. Member RODRIGO O DE VENECIA, JR.
VICTOR Membe	R.S. BAG.AYAN, JR.	ELISEO E. BRILLANTES Member
X	mending Approval:	Approved by:
GUILLE Chairpe	ERMO V. LUCERO rson	SALVADOR M. ROYECA General Manager

ROK 2.12