

  	<b>BAGUIO WATER DISTRICT</b> BWD Compound, Utility Road, Baguio City 2600	Document No.	ADM-PUR-F006
	<b>PURCHASE ORDER (P.O)</b>	Revision Date	October 29, 2019
		Revision No.	02

No 036438


Supplier / Contractor	: KEYLARGO INDUSTRIAL SALES	Purchase Order No.	: 36438
Contact Number	: 02-284-2856 / 961-52-60 local 218	Date	: December 10, 2024
Address / TIN	: 1471 Quezon Ave. West Triangle Q.C.	PR No. / Abstract No.	: 11-182P

Gentlemen / Madam,







Please furnish this Office the following articles subject to the terms and conditions contained herein.




Place of Delivery : <input type="checkbox"/> Pick-up <input checked="" type="checkbox"/> FOB BWD Warehouse <input type="checkbox"/> Deliver at Site: _____	Purchase Order (PO) Valid Until: 30 DAYS Warranty: <input type="checkbox"/> Six Months <input checked="" type="checkbox"/> One Year <input type="checkbox"/> Others (please specify) _____
Date of Delivery : _____ Working Days _____ Calendar Days upon receipt of PO 10-25 WEEKS	<input checked="" type="checkbox"/> 1% Retention Required <input type="checkbox"/> Performance Bond Required (5% if in check / 50% if GSIS surety bond) <input checked="" type="checkbox"/> Subject to testing / inspection prior to payment
Delivery Term : <input type="checkbox"/> Full <input type="checkbox"/> Partial Delivery allowed	Payment Term: <input type="checkbox"/> COD <input type="checkbox"/> 30 Days <input checked="" type="checkbox"/> Others (please specify) 60 DAYS

Quantity	Unit	Description / Specifications	Unit Cost	Amount
2	sets	<p>"Grundfos" (Denmark) Vertical Multistage Centrifugal Pump &amp; Motor Pump Model: CRN15-5 E-F-A-E-HQQE, 100 USGPM, 250 feet, coupled to Induction Motor 10HP, 230V/460V, 60Hz, 3600 RPM, 2 Poles, 3-Phase, Class F Insulation, 90.2% efficiency at full load, TEFC enclose class.</p> <p>Complete with Motor Control: "Danfoss" (Denmark) Soft Starter Motor Controller adaptable to Vertical Multistage Centrifugal Motor model: MCD60063BT5S1X20-CV2 Rating: 20HP, 240V (nominal), 3-Phase, 60Hz Capacity of Pressure Transmitter of: 25 bars Control Body: IP20 Enclosure (can be utilized as control shall be installed with in control panel)</p> <p>X-X-X-X-X-X-X-X-X-X-X-X</p> <p>(Please refer to the attached sheet for complete detailed speciifiactions)</p> <ul style="list-style-type: none"><li>- For on-site delivery</li><li>- Supplier to provide high tensile mounting bolts for pump base</li><li>- Supplier to provide BNG and flanges for both suction and discharge ports</li><li>- Supplier to provide manufacturer pump test result upon delivery</li><li>- Supplier to provide brochure with full specification and pump curve of offered booster pump</li></ul> <p>Note: Soft Starter should be equipped with SCADA ready device - Bidder to submit certificate os sole distributorship</p>	503,000.00 ₱	1,006,000.00

**EM-LED**  
16 DEC 2024

Usage / Requisitioner: For Ambiong rain basin booster

Prepared by:  PAUL RAJANO OIC, Purchasing Supervisor	Checked by:  ATTY. CHANELL DOLOR Admin. Division Manager	Audited by:  LUZVIMIN G. RAMOS Internal Audit	Recommending Approval:  ATTY. MARJORIE G. TENEDERO AGM Adm./Com./Fin.	Approved by:  ENGR. SALVADOR M. BOYECA General Manager
Conforme: _____		6/9/25		
Signature over Printed Name of Supplier		Date		
Funds Available:  JELYN V. PENALES Finance Manager	Acct.: Operating / Maintenance Expense <input type="checkbox"/> CAPEX <input checked="" type="checkbox"/> Other Payables <input type="checkbox"/>			

  	<b>BAGUIO WATER DISTRICT</b> <b>BWD Compound, Utility Road, Baguio City 2600</b>		Document No.	ADM-PUR-F006
	<b>PURCHASE ORDER (P.O)</b>		Revision Date	February 15, 2020
			Revision No.	00




Supplier/Contractor	: KEYLARGO INDUSTRIAL SALES	Purchase Order No.	: 36438
Contact Number	: 02-248-2856/961-52-60 local 218	Date	: December 10,2024
Address / TIN	: 1471 Quezon Ave. West Triangle Quezon City	PR No./Abstract No.	: 11-176P

Qty	Unit	Description	Unit Cost	Amount
2	sets	"GRUNDFOS" (Denmark) Vertical Multistage Centrifugal Pump and Motor Model: CRN15-5 E-F-A-E-HQQE Motor Specifications: - Type: Induction - HP Rating: 10HP - Nominal Voltage: 230V/460V - Supply Frequency: 60Hz - Number of Poles: 2 Poles - Nominal Speed: 3600 RPM - Number of Phase: 3Φ - Insulation Class: F - Efficiency at full load: 90.2% - Enclose Class: TEFC Coupled and aligned with Heavy Duty Mounting Base to: Pump Requirement: - Capacity: 100 USGPM - TDH: 250ft Construction Material: Shaft Seal: Cartridge Type Shaft Seal Material: HQQE Pump Head: Cast Iron / Stainless Steel (updated specs) Pump Shaft: Stainless Steel Impeller: Stainless Steel Chamber: Stainless Steel Outer Sleeve: Stainless Steel Base: Cast iron / Stainless Steel (updated specs) Neck Ring: Polyetheretherketone (PEEK) Support Bearing: PTFE Bearing Rings: Silicon Carbide Pump Efficiency: 76.1%  Complete with Motor Control: "Danfoss" (Denmark) Soft Starter Motor Controller adaptable to 20HP, 240V (nominal), 3 phase, 60Hz, Vertical motor model MCD60063BT5S2X20-CV2 Soft Starter Specifications:	503,000.00	1,003,000.00



EMAILED






16 DEC 2024

  	<b>BAGUIO WATER DISTRICT</b> <b>BWD Compound, Utility Road, Baguio City 2600</b>	<b>Document No.</b> ADM-PUR-F006
	<b>PURCHASE ORDER (P.O)</b>	<b>Revision Date</b> February 15, 2020
		<b>Revision No.</b> 00

Qty	Unit	Description	Unit Cost	Amount
		<b>1. Main Voltage</b>		
		L1, L2, L3 200VAC – 300VAC (+/- 10%)		
		<b>2. Control Voltage</b>		
		(A4, A6) 220-240VAC (+10% / -15%)		
		Main Frequency 60Hz (+/- 10%)		
		Rated insulation Voltage to earth 600VAC		
		Rated impulse withstand voltage 4kV		
		<b>3. Short Circuit Capability</b>		
		Coordination Semi-conductor fuses		
		Prospective current 65kA		
		<b>4. Outputs</b>		
		Relay outputs 10A @ 250VAC resistive		
		Programmable outputs 1 (NC), 1 (NO), 1 (CO)		
		Analogue outputs 4-20mA		
		Maximum load 600Ω (12VDC @ 20mA accuracy +/-5%)		
		24VDC output, maximum load 200mA (accuracy +/- 10%)		
		<b>5. Environmental</b>		
		Protection IP20 & NEMA, UL indoor type 1		
		Operating temperature -10°C to 60°C		
		Storage temperature -25°C to 60°C		
		<b>6. Heat Dissipation</b>		
		During start 4.5 watts per ampere		

Total: **₱1,006,000.00**

Usage: For Ambiong rain basin booster

<b>Prepared by:</b>  <u>P. A. Arjano</u> C-SMPO	<b>Checked by:</b> DEC 1  <u>Atty. C.D. De la Cruz</u> Administrative Director	<b>Audited by:</b>  <u>L. G. Ramos</u> Internal Auditor	<b>Recommending Approval:</b>  <u>Atty. M.L.C. Jenedero</u> AGM Adm./Com./Fin./ICT	<b>Approved by:</b>  <u>Engr. Salvador M. Royeca</u> General Manager
---	---	---	---	--



## RESOLUTION

Revision No. 00

By: *Signed*  
**Engr. Salvador M. Royeca**  
*General Manager*